

Docket No. AUS920010996US1

**DATA PROCESSING SYSTEM, METHOD, AND COMPUTER PROGRAM
PRODUCT FOR GENERATING A GENERIC COMPILATION INTERFACE
FROM OBJECT-ORIENTED CODE**

5

BACKGROUND OF THE INVENTION

1. Technical Field:

10 The present invention relates generally to the field of data processing systems and, more specifically to a data processing system, method, and computer program product for generating a generic compilation interface from object-oriented software code.

2. Description of Related Art:

15 Java is a commonly used programming language for the Internet or world wide web. Generally, home pages including hypertext references and reference pages are written in HTML (hypertext markup language). Network browsers installed at user terminals or network servers
20 are Java-enabled and have a Java virtual machine embedded in the browser to respond to Java programs. Applets are small programs which are designed to operate within Internet pages. Typically, the hypertext statement is underscored to indicate that its selection will effect
25 the display of a referenced item.

"Java Beans" are portable platform-independent components written in the Java programming language. "Java Beans" or "beans" are program components that may be used and reused in applets or other Java programs.
30 Java beans allow developers to create reusable software components that can be assembled together using visual application builder tools such as VisualAge by IBM.

10042079 010700

Docket No. AUS920010996US1

Integrated development environments (IDEs) are available to assist developers in authoring software code. An IDE is typically a software application which provides software components to quickly prototype a new application. Some IDEs, such as VisualAge for Java, are visual composition environments whereby a graphical user interface (GUI) is provided to the developer to further aid in the development process.

A problem often arises, however, when using an IDE. New code designed using the IDE often depends on features, packages, methods, fields, variables, or other software code from other packages that are not available within the IDE. In order for the development environment to incrementally compile the new code, it must resolve these references to the other packages.

One solution to this problem is to import the referenced code into the IDE. The referenced code may be stored in a JAR file, thus, requiring that the JAR file be imported. Java beans are packaged and delivered in JAR (Java Archive) files, which is a technology supported by JDK (Java Development Kit) 1.1. JAR files are used to collect Java class files, serialized objects, images, help files, and similar resource files. In many Internet sessions when a user is accessing or connected to a site in the World wide web, the user may need to or desire to acquire a program or other downloadable content, typically in the form of a JAR file, from that site.

The JAR file imported into the IDE, however, often also includes code that has references to yet other code which is not included in the specified JAR and is also not included in the IDE. Sometimes this problem is compounded because the referenced code may be native to

Docket No. AUS920010996US1

an operating system that is different and incompatible with the operating system on which the IDE is executing.

Therefore, a need exists for a method, system, and computer program product for generating a generic,
5 compilation Java Archive (JAR) file which may be easily imported into and used within an IDE.

202009010996US1

SUMMARY OF THE INVENTION

5 A data processing system, method, and computer
program product are disclosed for generating a generic
compilation interface from a first object-oriented
software package. All public classes included in the
object-oriented software package are identified. For
each of the public classes, all public entities included
in each of the public classes are identified. All
10 references to software defined in a second software
package are removed from the public entities. An
equivalent public class is then generated for each of the
identified public classes. Each equivalent public class
includes equivalent public entities that include no
15 references to software that is defined in the second
package. Each of the equivalent public classes is
compiled. A compilation interface is generated for the
object-oriented software package. The compilation
interface includes each of the compiled equivalent public
20 classes.

The above as well as additional objectives,
features, and advantages of the present invention will
become apparent in the following detailed written
description.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

10 **Figure 1** is a pictorial representation which depicts a data processing system in which the present invention may be implemented in accordance with the present invention;

15 **Figure 2** illustrates a block diagram of a computer system which may be utilized as a server computer system in accordance with the present invention;

Figure 3 depicts a block diagram of a computer system which may be utilized as a client computer system in accordance with the present invention; and

20 **Figure 4** illustrates a high level flow chart which depicts generating a generic compilation interface for object-oriented software code in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

5 A preferred embodiment of the present invention and its advantages are better understood by referring to the figures, like numerals being used for like and corresponding parts of the accompanying figures.

10 The present invention is a data processing system, method, and computer program product for generating a generic compilation interface from a first object-oriented software package. The software package is preferably object-oriented code stored in a Java Archive (JAR) file. After a particular JAR file is selected, the public classes included in the JAR file are identified.

15 For each of the listed public classes, all of the public entities included in each of the public classes are identified. For the purposes of this application, the term "entities" includes methods, parameters, fields, interfaces, and all other types software constructs, variables, components, or functions. Thus, public
20 entities are those entities that are publicly available, i.e. accessible by all other objects. A public entity typically is identified as such by the inclusion of the "public" modifier.

25 All references to software defined in other software packages are then removed from the identified public entities. An equivalent public class is then generated for each of the identified public classes. Each equivalent public class includes equivalent public
30 entities that include no references to software that is defined in other software packages. All "native" attributes are also removed. In addition, return

Docket No. AUS920010996US1

statements are included for methods which require return statements. When an original return statement includes a reference, a default value is substituted for the reference.

5 A separate output file is created for each of the equivalent public classes. All of the output files are then compiled. The compiled output files are stored in a JAR file which is then used as a generic, compilation interface for the original object-oriented software
10 package.

Because the generic JAR file does not include any references to software defined in other packages or native attributes, the file then can be imported into an IDE and compiled against without generating missing
15 reference errors. A developer may now write code to the generic JAR file and have the IDE incrementally compile the new code without displaying reference problems.

The following is a simplistic example of the present invention.

20 The following is a first JAR file, jar1.jar, that includes ExampleClass1 and a native method that can be executed only on a particular operating system:

```

package jar1;
public class ExampleClass1
25    {
        public ExampleClass1()
        {
        }
        public native boolean aMethod(String)
30    }

```

The following is a second JAR file, jar2.jar, that

Docket No. AUS920010996US1

includes an ExampleClass2 and a reference to the native method defined in the first JAR file:

```
package jar2;
import jar1.*;
5 public class ExampleClass2
{
    private ExampleClass1 var;
    public ExampleClass2()
    {
10         var = new ExampleClass1();
        var.aMethod("string");
    }
    public boolean bMethod(String A)
    {
15         return true;
    }
}

An application package may be developed, such as:
20 import jar2.ExampleClass2;
public class AppUsingJar2
{
    public AppUsingJar2()
    {
25         ExampleClass2 var = new ExampleClass2();
    }
}
```

This application package can be developed and compiled using the second JAR file, jar2.jar. However, 30 because the second JAR file includes a reference to a native method that is defined outside of the second JAR file, a dependency will exist that the IDE cannot

Docket No. AUS920010996US1

resolve, thus generating an error.

The present invention describes generating a generic, compilation JAR file that can be used within the IDE against which the application package can be compiled without generating a reference error. The generic, compilation JAR file can be generated from the second JAR file. The following is the generic, compilation JAR file the is generated from the second JAR file:

```

package jar2;
10 public class ExampleClass2()
    {
        public ExampleClass2()
        {
        }
15 public boolean bMethod(String a)
    {
        return true;
    }
    }

```

20 This generic, compilation JAR file includes only the public entities of the original second JAR file. All references to code defined in JAR files other than the second JAR file have been removed. Thus, the reference to "aMethod" has been removed. Although the output of generic, compilation JAR file is not executable, it can be compiled against during development of other code. The generic, compilation JAR file does not include any reference to other JAR files.

30 **Figure 1** depicts a pictorial representation of a network of data processing systems in which the present invention may be implemented. Network data processing system **100** is a network of computers in which the present

Docket No. AUS920010996US1

invention may be implemented. Network data processing system **100** contains a network **102**, which is the medium used to provide communications links between various devices and computers connected together within network data processing system **100**. Network **102** may include connections, such as wire, wireless communication links, or fiber optic cables.

In the depicted example, a server **104** is connected to network **102** along with storage unit **106**. In addition, clients **108**, **110**, and **112** also are connected to network **102**. Network **102** may include permanent connections, such as wire or fiber optic cables, or temporary connections made through telephone connections. The communications network **102** also can include other public and/or private wide area networks, local area networks, wireless networks, data communication networks or connections, intranets, routers, satellite links, microwave links, cellular or telephone networks, radio links, fiber optic transmission lines, ISDN lines, T1 lines, DSL, etc. In some embodiments, a user device may be connected directly to a server **104** without departing from the scope of the present invention. Moreover, as used herein, communications include those enabled by wired or wireless technology.

Clients **108**, **110**, and **112** may be, for example, personal computers, portable computers, mobile or fixed user stations, workstations, network terminals or servers, cellular telephones, kiosks, dumb terminals, personal digital assistants, two-way pagers, smart phones, information appliances, or network computers. For purposes of this application, a network computer is any computer, coupled to a network, which receives a

Docket No. AUS920010996US1

program or other application from another computer coupled to the network.

In the depicted example, server **104** provides data, such as boot files, operating system images, and applications to clients **108-112**. Clients **108**, **110**, and **112** are clients to server **104**. Network data processing system **100** may include additional servers, clients, and other devices not shown. In the depicted example, network data processing system **100** is the Internet with network **102** representing a worldwide collection of networks and gateways that use the TCP/IP suite of protocols to communicate with one another. At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers, consisting of thousands of commercial, government, educational and other computer systems that route data and messages. Of course, network data processing system **100** also may be implemented as a number of different types of networks, such as for example, an intranet, a local area network (LAN), or a wide area network (WAN). **Figure 1** is intended as an example, and not as an architectural limitation for the present invention.

Referring to **Figure 2**, a block diagram of a data processing system that may be implemented as a server, such as server **104** in **Figure 1**, is depicted in accordance with a preferred embodiment of the present invention. Data processing system **200** may be a symmetric multiprocessor (SMP) system including a plurality of processors **202** and **204** connected to system bus **206**. Alternatively, a single processor system may be employed. Also connected to system bus **206** is memory

Docket No. AUS920010996US1

controller/cache **208**, which provides an interface to local memory **209**. I/O bus bridge **210** is connected to system bus **206** and provides an interface to I/O bus **212**. Memory controller/cache **208** and I/O bus bridge **210** may be
5 integrated as depicted.

Peripheral component interconnect (PCI) bus bridge **214** connected to I/O bus **212** provides an interface to PCI local bus **216**. A number of modems may be connected to PCI bus **216**. Typical PCI bus implementations will
10 support four PCI expansion slots or add-in connectors. Communications links to network computers **108-112** in **Figure 1** may be provided through modem **218** and network adapter **220** connected to PCI local bus **216** through add-in boards.

15 Additional PCI bus bridges **222** and **224** provide interfaces for additional PCI buses **226** and **228**, from which additional modems or network adapters may be supported. In this manner, data processing system **200** allows connections to multiple network computers. A
20 memory-mapped graphics adapter **230** and hard disk **232** may also be connected to I/O bus **212** as depicted, either directly or indirectly.

Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 2** may vary. For
25 example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect to the present invention.

30 The data processing system depicted in **Figure 2** may be, for example, an IBM RISC/System 6000 system, a

Docket No. AUS920010996US1

product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive (AIX) operating system.

With reference now to **Figure 3**, a block diagram illustrating a data processing system is depicted in which the present invention may be implemented. Data processing system **300** is an example of a client computer. Data processing system **300** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used. Processor **302** and main memory **304** are connected to PCI local bus **306** through PCI bridge **308**. PCI bridge **308** also may include an integrated memory controller and cache memory for processor **302**. Additional connections to PCI local bus **306** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **310**, SCSI host bus adapter **312**, and expansion bus interface **314** are connected to PCI local bus **306** by direct component connection. In contrast, audio adapter **316**, graphics adapter **318**, and audio/video adapter **319** are connected to PCI local bus **306** by add-in boards inserted into expansion slots. Expansion bus interface **314** provides a connection for a keyboard and mouse adapter **320**, modem **322**, and additional memory **324**. Small computer system interface (SCSI) host bus adapter **312** provides a connection for hard disk drive **326**, tape drive **328**, and CD-ROM drive **330**. Typical PCI local bus implementations will support three or four PCI expansion

Docket No. AUS920010996US1

slots or add-in connectors.

An operating system runs on processor **302** and is used to coordinate and provide control of various components within data processing system **300** in **Figure 3**.

5 The operating system may be a commercially available operating system, such as Windows 2000, which is available from Microsoft Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provide calls to the
10 operating system from Java programs or applications executing on data processing system **300**. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on storage
15 devices, such as hard disk drive **326**, and may be loaded into main memory **304** for execution by processor **302**.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 3** may vary depending on the implementation. Other internal hardware or peripheral
20 devices, such as flash ROM (or equivalent nonvolatile memory) or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 3**. Also, the processes of the present invention may be applied to a multiprocessor data processing
25 system.

As another example, data processing system **300** may be a stand-alone system configured to be bootable without relying on some type of network communication interface, whether or not data processing system **300** comprises some
30 type of network communication interface. As a further example, data processing system **300** may be a Personal Digital Assistant (PDA) device, which is configured with

Docket No. AUS920010996US1

ROM and/or flash ROM in order to provide non-volatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 3** and above-described examples are not meant to imply architectural limitations. For example, data processing system **300** also may be a notebook computer or hand held computer in addition to taking the form of a PDA. Data processing system **300** also may be a kiosk or a Web appliance.

Figure 4 illustrates a high level flow chart which depicts generating a generic compilation interface for object-oriented software code in accordance with the present invention. The process starts as depicted by block **400** and thereafter passes to block **402** which illustrates selecting an object-oriented software package, such as a Java Archive (JAR) file. Next, block **404** depicts placing the selected runtime JAR file into the classpath on the runtime machine, such as data processing system **300**. The process then passes to block **406** which illustrates enumerating all of the classes that are included in the selected JAR file. One method for enumerating classes is the java.util.jar utility.

Block **408**, then, depicts getting the first class from the list created as illustrated by block **406**. Thereafter, block **410** illustrates listing all public entities, such as public methods, public parameters, and public fields included in the class. One method for listing all public entities of a class is Java's Reflection feature. "Reflection" is one of the application program interfaces (APIs) available as part of Java.

Docket No. AUS920010996US1

The process then passes to block **412** which depicts getting the first entity, such as a method, parameter, or field included in the list created as illustrated by block **410**. Thereafter, block **414** illustrates removing
5 all references to software that is defined in a different software package from the entity, i.e. the method, parameter, or field. Next, block **416** depicts removing the "native" attribute if such an attribute is included. Block **418**, then, illustrates including a return
10 statement, with a default value if necessary, if the entity was a method that requires a return statement.

The process then passes to block **420** which depicts a determination of whether or not this is the last entity, i.e. last method, parameter, or field in the class. If a
15 determination is made that this is not the last entity in the class, the process passes to block **422** which illustrates getting the next entity, i.e. the next method, parameter, or field in the class. The process then passes back to block **414**.

Referring again to block **420**, if a determination is made that there are no more entities in this class, the process passes to block **424** which depicts emitting an output file for this class. Preferably, the output file will be a ".java" file. The .java file will include
25 equivalent entities to those included in the specified JAR file, as well as any required return statements. Next, block **426** illustrates a determination of whether or not this is the last class in the JAR file. If a determination is made that this is not the last class in
30 the JAR file, the process passes to block **428** which depicts getting the next class. The process then passes back to block **410**.

Referring again to block **426**, if a determination is made that this is the last class in the JAR file, the process passes to block **430** which illustrates compiling all of the output .java files. Next, block **432** depicts
5 generating a generic, compilation JAR file that includes all of the compiled .java files. The process then terminates as illustrated by block **434**.

It is important to note that while the present invention has been described in the context of a fully
10 functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention
15 applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and
20 transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded
25 formats that are decoded for actual use in a particular data processing system.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the
30 invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in

Docket No. AUS920010996US1

order to best explain the principles of the invention,
the practical application, and to enable others of
ordinary skill in the art to understand the invention for
various embodiments with various modifications as are
5 suited to the particular use contemplated.

2020010996US1